

SRK-HG Wall mounted fixed speed

- Fixed speed heat pump split system
- Low noise levels
- Fully pre-charged with refrigerant for maximum piping up to 15m



INDOOR UNIT c/w IR Controller		SRK28HG-S	SRK40HG-S
OUTDOOR UNIT		SRC28HG-S	SRC40HG-S
Cooling (Nominal)	kW	2.6	3.6
UK Cooling	kW	2.5	3.5
UK Sensible Cooling	kW	1.9	2.7
E.E.R. (Energy Label)		3.21 (B)	3.21 (B)
Heating (Nominal)	kW	2.8	3.9
C.O.P (Energy Label)		3.64 (B)	3.41 (B)
Operating Range (Outdoor Air) Cooling	°C DB	21 to 43	
Operating Range (Outdoor Air) Heating	°C WB	-5 to 21	

INDOOR UNIT			
Exterior Dimensions (H x W x D)	mm	268 x 790 x 199	268 x 790 x 199
Net Weight	kg	8.5	8.5
Air Volume (High Speed) Cooling	m ³ /s	0.14	0.15
Air Volume (High Speed) Heating	m ³ /s	0.17	0.17
Sound Pressure Level* (L/M/H) Cooling	dB(A)	30 / 33 / 39	34 / 38 / 40
Sound Pressure Level* (L/M/H) Heating	dB(A)	29 / 33 / 40	34 / 38 / 40

OUTDOOR UNIT			
Exterior Dimensions (H x W x D)	mm	540 x 780(+62) x 290	540 x 780(+62) x 290
Net Weight	kg	31	38
Sound Power Level	dB(A)	60	63

ELECTRICAL DATA			
Power Source Rating MCB	A	25	32
Mains Power To	230V/1ph/50Hz	Indoor	Indoor
Interconnecting Wires		3 + E	3 + E
Running Current - Cooling	A	3.7	5.2
Running Current - Heating	A	3.5	5.3
Power Input - Cooling	kW	0.81	1.12
Power Input - Heating	kW	0.77	1.15
Start Current	A	16.4	27.0

INSTALLATION/REFRIGERANT			
Ref. Piping Size o.d ins (mm)	Liquid	1/4" (6.35)	1/4" (6.35)
	Gas	3/8" (9.52)	1/2" (12.7)
Ref. Max Piping Length	m	15	15
Vertical Height Difference (Max)			
- Outdoor Unit Above Indoor Unit	m	10	10
- Outdoor Unit Below Indoor Unit	m	10	10
Refrigerant Amount Precharged	kg	0.85	1.15
- For Pipe Length Up To	m	15	15
Additional Refrigerant	g/m	n/a	n/a

RETAIL PRICE			
Indoor Unit		£145	£180
Outdoor Unit		£305	£330
SYSTEM PRICE		£450	£510

A low ambient controller should be fitted for UK operation otherwise the warranty may be affected.

** Sound Pressure Level fan speeds: LOW/MED/HIGH measured at 1m below.